



# FASTENERS

## Wood Screw

Foam-Control® Wood Screws are used to attach Foam-Control Nailbase/Nailstrip to wood structural members and substrates.

- Available in standard\* lengths from 3" - 13"

## Metal Screw

Foam-Control® Metal Screws are used to attach Foam-Control Nailbase/Nailstrip to lightweight (up to 18 gauge) steel structural members and substrates.

- Available in standard\* lengths from 3" - 13"

## Concrete Screw

Foam-Control Concrete Screws are used to attach Foam-Control Nailbase/Nailstrip to all concrete structural members and substrates. Foam-Control Concrete Screws are installed into predrilled 3/16" holes.

- Available in standard\* lengths from 3" - 13"

## Fluted Concrete Nail

Foam-Control Concrete Nails are used to attach Foam-Control Nailbase/Nailstrip to poured concrete structural members and substrates. Foam-Control Concrete Nails are installed into predrilled 3/16" holes.

- Available in standard\* lengths from 3" - 8"

\* Contact your Foam-Control supplier for availability of additional length fasteners.

# FOAM-CONTROL NAILBASE/NAILSTRIP ACCESSORY



## CONTROL, NOT COMPROMISE.®

**Foam-Control Screws and Fluted Concrete Nails are engineered and manufactured to give you control over every aspect of your project installation.**

- Sit tight to the Foam-Control Nailbase/Nailstrip surface
- Heat treated steel for high strength and durability
- Coated for superior corrosion resistance
- 6 lobe drive design for screws
- Fluted nail design makes for ease of installation and grab

### Wood Screw




Head Style	0.625" Pancake head
Drive Style	T-30, 6 lobe
Thread/Shank Diameter	0.255" / 0.190"
Thread Length <sup>1</sup>	2.75" for 4.0"+ screws
Point Style	Gimlet Thread

### Concrete Screw



Head Style	0.625" Pancake head
Drive Style	T-30, 6 lobe
Thread/Shank Diameter	0.255" / 0.190"
Thread Length	2.75"
Predrill Hole	3/16" masonry bit

### Metal Screw



Head Style	0.625" Pancake head
Drive Style	T-30, 6 lobe
Thread/Shank Diameter	0.255" / 0.190"
Thread Length	2.75"
Point Style	#2 Drill Point

### Fluted Concrete Nail



Head Style	0.4375" Pancake head
Flute/Shank Diameter	0.210" / 0.202"
Flute Length <sup>1</sup>	4.0" for 4.5"+ nails
Predrill Hole	3/16" masonry bit

1. Contact your Foam-Control supplier for thread/flute length on shorter screws/nails.

### Specifications/Installation

Fasteners as shown on plans and in specifications shall be supplied by the Foam-Control supplier.

Use Foam-Control screws and/or nails per Foam-Control recommended installation guidelines. Refer to Foam-Control Construction Manuals and Technical Bulletins showing proper design and applications.

### Foam-Control Accessory Availability

Your nearest Foam-Control supplier will be happy to collaborate with you to determine your needs for Foam-Control Accessories. For additional information on Foam-Control Nailbase/ Nailstrip and to contact your nearest supplier visit [www.Foam-Control.com](http://www.Foam-Control.com).



**501-945-1114 phone**  
**501-945-2583 fax**  
**noark@noarkrcontrol.com**  
**www.noarkrcontrol.com**



Foam-Control EPS products are manufactured by AFM Corporation licensees.

Copyright © 2011 AFM Corporation. All rights reserved. Printed in USA. Control, Not Compromise and Foam-Control are registered trademarks of AFM Corporation, Lakeville, MN.

FCN04-02/11



**CONTROL,  
NOT COMPROMISE.®**